Printing date 13.04.2023

Version number 16 (replaces version 15)

Revision: 13.04.2023

· 1.1 Product identifier	
· Product name FloorCare matt/satin	
• Article number: 10490-3-000 • 1.2 Relevant identified uses of the substance or mixture and No further relevant information available. • Application of the substance / the mixture Self glazing emulsi	-
• 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier: LOBA GmbH & Co. KG Leonberger Straβe 56 - 62 D-71254 Ditzingen	Tel.: +49 (0)7156/3
 Informing department: service@loba.de 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number):GBK GmbH +49 (0)6132-84463
SECTION 2: Hazards identification	
 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 	
Aquatic Chronic 3 H412 Harmful to aquatic life with long las	sung ejjecis.
• 2.2 Label elements • Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CL • Hazard pictograms Void	P regulation.
• Signal word Void • Hazard statements	
H412 Harmful to aquatic life with long lasting effects.	
• Precautionary statements	
P101 If medical advice is needed, have product container or la	abel at hand.
P102 Keep out of reach of children.	
P103 Read carefully and follow all instructions.	
P273 Avoid release to the environment. P501 Dispose of contants/container in accordance with local/	magional/mational/intermational negulations
<i>P501 Dispose of contents/container in accordance with local/</i> • <i>Additional information:</i>	regional/national/international regulations.
EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-i methyl-2H-isothiazol-3-one [EC no. 220-239-6] produce an allergic reaction.	
· 2.3 Other hazards	
 <i>Results of PBT and vPvB assessment</i> <i>PBT:</i> Not applicable. <i>vPvB:</i> Not applicable. 	

· 3.2 Mixtures

• Description: Mixture of the substances listed below with harmless additions.

(Contd. on page 2) GB

Printing date 13.04.2023

Version number 16 (replaces version 15)

Revision: 13.04.2023

Product name FloorCare matt/satin

Dangerous components:		
CAS: 38714-47-5	tetraamminezinc(2+) carbonate	≥ 0.25-<1%
EINECS: 254-099-2 Reg.nr.: 01-2120760626-49	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-	≥0.00025-<0.0015%
EC number: 911-418-6	one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-	
Index number: 613-167-00-5	one [EC no. 220-239-6] (3:1)	
Reg.nr.: 01-2120764691-48	Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox.	
	2, H330; 🚯 Skin Corr. 1C, H314; Eye Dam. 1, H318;	
	Aquatic Acute 1, H400 (M=100); Aquatic Chronic	
	1, H410 (M=100); 🚯 Skin Sens. 1A, H317	
	Specific concentration limits:	
	<i>Skin Corr. 1C; H314: C</i> ≥0.6 %	
	Skin Irrit. 2; H315: $0.06 \% \le C < 0.6 \%$	
	<i>Eye Dam. 1; H318: </i> $C \ge 0.6 \%$	
	<i>Eye Irrit.</i> 2; H319: $0.06 \% \le C < 0.6 \%$	
	Skin Sens. 1A; H317: C ≥ 0.0015 %	

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation Supply fresh air; consult doctor in case of symptoms.

• *After skin contact The product is not skin irritating.*

· After eye contact Rinse opened eye for several minutes under running water.

· After swallowing In case of persistent symptoms consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

• 5.1 Extinguishing media

• Suitable extinguishing agents Use fire fighting measures that suit the environment.

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

• 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Not required.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system. Dilute with much water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

• 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

(Contd. on page 3)

Printing date 13.04.2023

Version number 16 (replaces version 15)

Revision: 13.04.2023

Product name FloorCare matt/satin

(Contd. of page 2)

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions necessary if used correctly.
- Information about protection against explosions and fires: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers: No special requirements.
- Information about storage in one common storage facility: Not required.
- \cdot Further information about storage conditions: None.
- · Storage class 12
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures Wash hands during breaks and at the end of the work.
- Breathing equipment: Not required.
- · Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves
- Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.4 mm

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

Value for the permeation: Level ≤ 6

· Eye/face protection Safety glasses recommended during refilling.

9.1 Information on basic physical and cl	hemical properties	
General Information		
· Physical state	Fluid	
· Colour:	White	
· Smell:	Recognisable	
· Odour threshold:	Not determined.	
• Melting point/freezing point:	Not determined	
· Boiling point or initial boiling point and	boiling	
range	100 °C	

Printing date 13.04.2023

Version number 16 (replaces version 15)

Revision: 13.04.2023

Product name FloorCare matt/satin

	(Contd. of page
Flammability	Not applicable.
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable
Decomposition temperature:	Not determined.
pH at 20 °C	8.5
Viscosity:	
Kinematic viscosity	Not determined.
Kinematic viscosity	
dynamic:	Not determined.
Solubility	
Water:	Fully miscible
Partition coefficient n-octanol/water (log value)	Not determined.
Steam pressure:	Not determined.
Vapour pressure:	1101 weter minew.
Density and/or relative density	
Density at 20 °C	1.024 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
	Not determined.
9.2 Other information	
Appearance:	F 1: 1
Form:	Fluid
Important information on protection of health an	a
environment, and on safety.	
Self-inflammability:	Product is not selfigniting.
Explosive properties:	Product is not explosive.
Solids content:	15.7 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classe	25
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable	
	Void
gases in contact with water	Void Void
gases in contact with water Oxidising liquids	Void
gases in contact with water Oxidising liquids Oxidising solids	Void Void
gases in contact with water Oxidising liquids	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known

• 10.4 Conditions to avoid No further relevant information available.

(Contd. on page 5)

⁻ GB

Version number 16 (replaces version 15)

Revision: 13.04.2023

(Contd. of page 4)

Product name FloorCare matt/satin

Printing date 13.04.2023

· 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Oral	LD50	457 mg/kg (rat)
	LD50	660 mg/kg (rat)
Inhalative	LC50/4 h	0.33 mg/l (rat)
	LC50/96 h	0.188 mg/L (fish)

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- STOT-single exposure Based on available data, the classification criteria are not met.
- $\cdot \textit{STOT-repeated exposure} \textit{ Based on available data, the classification criteria are not met.}$
- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards

• Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

EC50/48 h 0.1 mg/L (daphnia)

EC50/72 h 0.027 mg/L (Algae)

NOEC 0.0012 mg/L (Algae) 0.004 mg/L (daphnia)

0.098 mg/L (fish)

· 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- *PBT:* Not applicable.

· vPvB: Not applicable.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

(Contd. on page 6)

GB

Printing date 13.04.2023

Version number 16 (replaces version 15)

Revision: 13.04.2023

(Contd. of page 5)

Product name FloorCare matt/satin

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

• 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport informat		
14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	Void	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according instruments	g to IMO Not applicable.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations

• Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Alteration in the context will be marked with a cross (*).

(Contd. on page 7)

GB

Printing date 13.04.2023

Version number 16 (replaces version 15)

Product name FloorCare matt/satin

	(Contd. of page 6
Relevant phrases	
H301 Toxic if swallowed.	
H310 Fatal in contact with skin.	
H314 Causes severe skin burns and eye damage.	
H315 Causes skin irritation.	
H317 May cause an allergic skin reaction.	
H318 Causes serious eye damage.	
H319 Causes serious eye irritation.	
H330 Fatal if inhaled.	
H400 Very toxic to aquatic life.	
H410 Very toxic to aquatic life with long lasting effects.	
Classification according to Regulation (EC) No 1272/2008	
The classification of the mixture is generally based on the calcu	lation method using substance data accordin
to Regulation (EC) No 1272/2008.	0
Department issuing data specification sheet: Product safety	
Abbreviations and acronyms:	Construction of Construction o
ADR: Accord relatif au transport international des marchandises danger International Carriage of Dangerous Goods by Road)	euses par route (European Agreement Concerning th
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemica	als
<i>EINECS: European Inventory of Existing Commercial Chemical Substances</i> <i>ELINCS: European List of Notified Chemical Substances</i>	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative Acute Tox. 3: Acute toxicity – Category 3	
Acute Tox. 2: Acute toxicity – Category 2	
Skin Corr. 1C: Skin corrosion/irritation – Category 1C	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
<i>Eye Irrit. 2: Serious eye damage/eye irritation – Category 2</i> <i>Skin Sens. 1: Skin sensitisation – Category 1</i>	
Skin Sens. 14: Skin sensitisation – Category 1A	
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard	
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic	e hazard – Category 3
* Data compared to the previous version altered.	