Tel.: +49 (0)7156/357-0

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.03.2024 Version number 26 (replaces version 25) Revision: 26.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Product name B1 Härter für alle Lacke A1 / Hardener for all finishes A1
- · Article number: 11467-B1-000
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

LOBA GmbH & Co. KG

Leonberger Straße 56 - 62

D-71254 Ditzingen

United Kingdom:

Phi House

Southampton Science Park

Southampton, SO167NS

United Kingdom

Phone +442380766722

- · Informing department: service@loba.de
- · 1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Hexamethylene diisocyanate homopolymer

2-butoxyethyl acetate

hexamethylene diisocyanate

· Hazard statements

H332 Harmful if inhaled.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

(Contd. on page 2)

Printing date 26.03.2024 Version number 26 (replaces version 25) Revision: 26.03.2024

Product name B1 - Härter für alle Lacke A1 / Hardener for all finishes A1

(Contd. of page 1)

P280 Wear protective gloves / eye protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH204 Contains isocyanates. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- Description: Mixture of the substances listed below with harmless additions.

| · Dangerous components: | | |
|--|---|---------|
| CAS: 160994-68-3 EC number: 679-501-7 | Hexamethylene diisocyanate homopolymer Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412 | 50-100% |
| CAS: 112-07-2 EINECS: 203-933-3 Index number: 607-038-00-2 Reg.nr.: 01-2119475112-47-xxxx | 2-butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332 | 5-8.5% |
| CAS: 822-06-0 EINECS: 212-485-8 Index number: 615-011-00-1 Reg.nr.: 01-2119457571-37- 0000/5/6 | hexamethylene diisocyanate Acute Tox. 1, H330; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 % | |

[·] Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

- · After skin contact Wash off immediately with soap and water and rinse thoroughly.
- · After eye contact Rinse opened eye for several minutes under running water.
- · After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Symptom Treat omatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 26.03.2024 Version number 26 (replaces version 25)

Product name B1 - Härter für alle Lacke A1 / Hardener for all finishes A1

(Contd. of page 2)

Revision: 26.03.2024

- · 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- ·Storage
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

112-07-2 2-butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm

Sk

· Ingredients with biological limit values:

822-06-0 hexamethylene diisocyanate

BMGV 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period od exposure

Parameter: isocyanate-derived diamine

- Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

Keep away from foodstuffs, beverages and food.

(Contd. on page 4)

Printing date 26.03.2024 Version number 26 (replaces version 25) Revision: 26.03.2024

Product name B1 - Härter für alle Lacke A1 / Hardener for all finishes A1

(Contd. of page 3)

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Breathing equipment:

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

· Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

Value for the permeation: Level ≤ 6

· Eve/face protection Safety glasses recommended during refilling.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

• Physical state Fluid

• Colour: According to product specification

Smell: Recognisable
 Odour threshold: Not determined.
 Melting point/freezing point: Not determined

· Boiling point or initial boiling point and boiling

range Not determined
Flammability Not applicable.
Lower: Not determined.
Upper: Not determined.

• Flash point: 65 °C (DIN EN ISO 3679)

• Decomposition temperature: Not determined. • pH Not determined.

· Viscosity:

· Kinematic viscosity at 20 °C 31-37 s (DIN 53211/4) dynamic: Not determined.

·Solubility

• Water: Not miscible or difficult to mix

• Partition coefficient n-octanol/water (log value) Not determined. • Steam pressure: Not determined.

· Density and/or relative density

• **Density at 20 °C** 1.095 g/cm³ (Dichtekugel 10ml 20°C)

Relative density

Vapour density

Not determined.

Not determined.

· Particle characteristics not applicable, as liquid

(Contd. on page 5)

Printing date 26.03.2024 Version number 26 (replaces version 25) Revision: 26.03.2024

Product name B1 - Härter für alle Lacke A1 / Hardener for all finishes A1

(Contd. of page 4)

9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and

environment, and on safety.

Self-inflammability: Product is not selfigniting.
 Explosive properties: Product is not explosive.
 Solids content: 75.0 %

Change in condition

Change in Condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void Void · Flammable solids · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable Void gases in contact with water Void · Oxidising liquids Void · Oxidising solids · Organic peroxides Void · Corrosive to metals Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

· Desensitised explosives

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Void

· 10.3 Possibility of hazardous reactions

Reacts with alcohols, amines, aqueous acids and alkalis

Reacts with water

Danger of bursting

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if inhaled.

| · LD/LC50 | values that | t are relevant for classification: |
|------------|-------------|------------------------------------|
| 160994-68 | 3-3 Hexam | ethylene diisocyanate homopolymer |
| Inhalative | ATE | 1.5 mg/l (rec) |
| 112-07-2 | 2-butoxyeti | hyl acetate |
| Oral | LD50 | 2,400 mg/kg (rat) |
| Dermal | LD50 | 1,580 mg/kg (rabbit) |
| | | (Contd. on maga 6) |

(Contd. on page 6)

Version number 26 (replaces version 25) Printing date 26.03.2024

Product name B1 - Härter für alle Lacke A1 / Hardener for all finishes A1

(Contd. of page 5)

Revision: 26.03.2024

| | | (Conta. or pag | $e_{\mathcal{S}_j}$ |
|------------|------------|--------------------|---------------------|
| 822-06-0 h | iexamethyl | lene diisocyanate | |
| Oral | LD50 | 959 mg/kg (rat) | |
| | ATE | 746 mg/kg (rec) | |
| Dermal | LD50 | >7,000 mg/kg (rat) | |
| Inhalative | LC50/4 h | 0.124 mg/l (rat) | |
| | ATE | 0.124 mg/l (rec) | |

- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · STOT-single exposure May cause respiratory irritation.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

| · 14.1 UN number or ID number | | |
|---|------|--|
| · 14.1 ON number of 1D number · ADR, ADN, IMDG, IATA | Void | |
| · 14.2 UN proper shipping name | | |
| · ADR, ADN, IMDG, IATA | Void | |

Revision: 26.03.2024

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.03.2024 Version number 26 (replaces version 25)

Product name B1 - Härter für alle Lacke A1 / Hardener for all finishes A1

(Contd. of page 6) · 14.3 Transport hazard class(es) · ADR, ADN, IMDG, IATA · Class Void · 14.4 Packing group · ADR, IMDG, IATA Void · 14.5 Environmental hazards: Not applicable. · 14.6 Special precautions for user Not applicable. · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. · UN "Model Regulation": Void

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Alteration in the context will be marked with a cross (*).

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H412 Harmful to aquatic life with long lasting effects.
- EUH204 Contains isocyanates. May produce an allergic reaction.

(Contd. on page 8)

Printing date 26.03.2024

Version number 26 (replaces version 25)

Product name B1 - Härter für alle Lacke A1 / Hardener for all finishes A1

(Contd. of page 7)

Revision: 26.03.2024

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- · Department issuing data specification sheet: Product safety
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 1: Acute toxicity - Category 1

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.

GB