

**LOBADUR** 

# 2K InvisibleProtect

**ADVANCED  
TECHNOLOGY**

Invisible surface protection

## Inspired by natural wood – invisible protection

If you walk on it barefoot, you'll just love it!

High-quality and innovative raw materials are the key to making LOBADUR 2K InvisibleProtect a truly unique surface coating. The wood looks and feels untreated and offers you all the protection of a finished floor. High durability and easy cleaning combine to make LOBADUR 2K InvisibleProtect the perfect surface treatment for all lovers of natural wood.



## Why end users are convinced of 2K InvisibleProtect :

- Invisible protection – the look, feel and color of the wood remain as if it was untreated
- Long-lasting natural beauty – high resistance to mechanical wear and household chemicals
- Simple and convenient cleaning
- Very low emission
- Time saving – light use after 24 hours, fully resistant after only 5 days

## Why contractors are enthusiastic about 2K InvisibleProtect :

- Excellent application performance – safe and easy to use
- Full build-up in two layers, no primer needed
- Very low emission, EMICODE EC1 PLUS R
- Low VOC, GISCODE W2/DD+
- Certified anti-slip according to BGR 181 and DIN 51130, evaluation class R9

## Special feature

LOBADUR 2K InvisibleProtect is a unique surface treatment. In addition to being invisible, it also feels incredibly like untreated wood. The latest generation of raw materials guarantees that the floor will be long-lasting and will not be polished up even under heavy wear.

## Range of use

Suitable for wood and cork floors. For heavy traffic residential areas and commercial use.



## Application

- Sand and remove dust from the surface properly
- First coat 2K InvisibleProtect with LOBATool roller Deluxe 120
- Intermediate sanding after 8-10 hours with LOBATool perforated pad P180 or finer
- Second coat 2K InvisibleProtect with LOBATool roller Deluxe 120
- Optionally a third coat of 2K InvisibleProtect after another intermediate sanding
- The consumption per coat is approx. 110-130 g/m<sup>2</sup>

**Art.-no.** 11474-000005

**Available** in 1kg and 5kg

**GISCODE** W2/DD+

LOBA is always at your side and ensures your success with both advice and action. Our experienced experts are happy to support you individually with your projects. Our competent technical service team is at your disposal quickly, if you need hands-on assistance on site. You can always rely on us!

**Please consider the detailed technical information, application advices and set-up recommendations.**

Do you have any questions? Do not hesitate to contact us:

Technical Information



**LOBA GmbH & Co. KG**

Leonberger Str. 56-62 | 71254 Ditzingen | Germany | Fon: +49 7156 357-0 | Fax: +49 7156 357-211 | E-Mail: service@loba.de | www.loba.de/en