TECHNICAL INFORMATION

# FactoryBase

PRIMER

Water-based roller primer for cement-based levelling compounds for direct use.

- Easy and safe application
- Time efficient through application in a 2-coat system (1x primer 1x finish)
- Optimizes adhesion between levelling compound and finish
- Applicable in a system with LOBA 2K FactoryStyle and numerous levelling compounds

**Range of use:**

Suitable for finishing cementitious floor levelling compounds for direct use approved by LOBA. You can find a corresponding list at: www.loba.de/en/Suitability-list/Factory-Line.

## Technical Data

| ART.-NO. | | | |
|---|---|---|---|
| 11751 | 5l | 4 | 128 |

| | |
|---|---|
| **Solids** | 24 ±2% |
| **Viscosity DIN 4** | 22 ±2s |
| **Storage and transportation** | 12 months of storage stability. No hazardous material according to ADR. Store and transport between +5 to +25°C. Protect from frost. |
| **GISCODE** | W2+ |
| **2004/42/CE** | EU limit value for this product (cat. A/i): 140 g/l (2010). This product contains max. 51 g/l VOC. |

## Application

- The cement-based leveling compound must be prepared for direct use according to the manufacturer's instructions.
- The floor must be dry and free of any previous layers, oil, grease, wax, silicone or any other impurities. Optimum working conditions: room temperature of +15°C - +25°C, floor

13/01/2024

## Application

temperature of +15°C - +22°C, 40% - 75% relative humidity, material temperature of +18°C - +25°C. Working areas must be adequately ventilated.

- Transfer material to a LOBA varnish bucket before applying.
- Stir the material well.
- To reduce the risk of excessive swelling, we recommend applying a maximum of 2 roll applications per day.
- Observe general and, if necessary, product-specific occupational health and safety regulations. Further information can be found in the GISCODE-related operating instructions which are available under www.wingis-online.de.
- This product is part of the LOBA and Wakol "Connected Systems" for finishing cementitious levelling compounds. The approved combinations can be found at



**LOBA GmbH & Co. KG** | Leonberger Str. 56-62 | 71254 Ditzingen | Germany | Tel.: +49 7156 357-0 | service@loba.de | www.loba.de

## General guidelines

**Cleaning of tools:** Clean tools and equipment immediately with water.

**Drying time:** The indicated drying times are valid for +20°C and 50% relative humidity, and assume careful, draught-free ventilation of the working area. Lower temperatures, higher relative humidity or poorer ventilation lead to longer drying times. Do not apply any protective coverings, wet clean the surface or lay carpet until the coating has achieved its final hardening. Product-specific data can be found in the relevant technical information.

**Interactions:** Materials such as carpet underlays, furniture legs, castors can lead to softening and discoloration. Exposure to hair dyes or rubber tyres on cars, motorcycles and cycles can lead to permanent, irreversible discoloration of the surface.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to Spezial conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe recommendations of cementitious leveling compound manufacturer and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.

Find further information on the subject of "cementitious leveling compound floors" in the leaflet of the BSR Bundesverband der vereidigten Sachverständigen für Raum und Ausstattung e.V.

13/01/2024